

GUELL 4 S/W




Part number	06210094
Lampholder:	LED
Light Source:	LED
Wattage:	430 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	SYMMETRIC WIDE REFLECTOR
Lightsource lumen output:	58452 lm
Luminaire lumen output:	50573 lm
L:	L70
B:	B10
Lifetime:	130000 h
Ta MIN luminaire:	-30°
Ta MAX luminaire:	30°
ULR:	0%
IPEA* (Street Lighting):	A+
IPEA* (Area Lighting):	A4+
IPEA* (Cycle/Pedestrian Lighting):	A++
IPEA* (Green Areas):	A++
IPEA* (Historical Areas):	A6+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Anti-aging silicone gasket
 - Electrical connection box in black technopolymer
 - Cable gland for cables $\varnothing 7 - \varnothing 17$ mm
 - Dimmable driver 1-10 V ballast
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Steel bracket, hot galvanised and painted in polyester powder
 - Cataphoresis and polyester powder coated steel sheet gear housing
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings




OPTIONAL ACCESSORIES

GUELL 4 A/W - S/W



14465794
Vetro soft GUELL 4

GUELL 4



14452702
Protective grid