

## GUELL ZERO S/M




<b>Part number</b>	06148985
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	15 W
<b>Finish:</b>	WH-RAL9010 / White RAL9010 / Glossy
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK06 1.2J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Symmetric medium reflector
<b>Lightsource lumen output:</b>	1888 lm
<b>Luminaire lumen output:</b>	1484 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	150000 h
<b>Ta MIN luminaire:</b>	-15°
<b>Ta MAX luminaire:</b>	35°
<b>ULR:</b>	0%
<b>IPEA* (Street Lighting):</b>	A++
<b>IPEA* (Area Lighting):</b>	A3+
<b>IPEA* (Cycle/Pedestrian Lighting):</b>	A++
<b>IPEA* (Green Areas):</b>	A++
<b>IPEA* (Historical Areas):</b>	A5+
<b>Luminous Intensity Class:</b>	G*6



### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating ISO 9227
  - Flat tempered glass diffuser
  - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
  - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
  - Stainless steel external screws
  - Stainless steel locking springs for the glass
  - Powder coated steel bracket
  - Complete with 1 metre of cable H05RN-F 3G1 mm<sup>2</sup>
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

