

HEDO+ FT C/EW



| | |
|---|------------------------------------|
| Part number | 3104710 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 25 W |
| Finish: | AN-96 / Anthracite gray / Textured |
| Insulation class: | II |
| Degree of protection: | IP66 |
| IK-J-xxIP: | IK08 5J xx5 |
| CRI: | 70 |
| Kelvin: | 4000 |
| Power factor: | $\text{COS}\phi \geq 0,9$ |
| Optic: | Extra wide circle reflector |
| Lightsource lumen output: | 4175 lm |
| Luminaire lumen output: | 3024 lm |
| L: | L90 |
| B: | B10 |
| Lifetime: | 100000 h |
| Ta MIN luminaire: | -20° |
| Ta MAX luminaire: | 50° |
| ULR: | 0% |
| IPEA* (Street Lighting): | A5+ |
| IPEA* (Area Lighting): | A6+ |
| IPEA* (Cycle/Pedestrian Lighting): | A5+ |
| IPEA* (Green Areas): | A5+ |
| IPEA* (Historical Areas): | A9+ |
| Luminous Intensity Class: | G*6 |




Description

Post-mounting outdoor luminaire, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating ISO 9227
- Painted die-cast aluminium pole-mounting joint for pole \varnothing 60 mm or 76 mm
- Extra-clear flat tempered glass diffuser internally screen-printed
- High resiliency anti-ageing silicone gasket with high elastic return capacity
- Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables \varnothing 9 - \varnothing 12 mm
- Light beam obtained by the combination of multiple LED modules
- Compliant with the UNI 10819 Standard and with the Italian regional laws on light pollution
- Stainless steel external screws
- Complete with supplementary device for protection against network surges of up to 10 kV (DM)
- Consult factory for other colour temperatures and colour rendering index
- Automatic power reduction version
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

