

HORO 2000 A/W




Part number	01062594
Lampholder:	E40
Light Source:	METAL HALIDE LAMPS
Wattage:	1x2000 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 65
IK-J-xxIP:	IK09 12J xx7
Optic:	Asymmetric Wide Reflector
Ta MIN luminaire:	-30°
Ta MAX luminaire:	25°




Description

- Discharge lamp floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Extra pure polished aluminium reflectors
 - Anti-ageing silicone gasket
 - Electrical connection box in black technopolymer
 - E40 porcelain lamp holder
 - Stainless steel locking springs for the glass
 - Stainless steel external screws
 - Fully integrated stainless steel safety spring clips
 - Mounting bracket in hot dip galvanised steel
 - Patented anti-vacuum device
 - Adequate power supply units, available as accessories, must be used for all floodlights

PHOTOMETRIC DATA



TECHNICAL DRAWINGS



CONTROL GEAR

HORO 2000 HQI-TS D/S / HQI-TS N/L / MHN-LA / MHN-FC



14020601
Power supply unit 400 V - 50 Hz, class I, on galvanised steel plate for 2000W metal halide lamps (not for HQI-TS and HQI-TS High Flux) with fuse and without ignitor



14014420
Set including power supply unit and power-factor capacitor for 2000W HQI-TS 400V 50 Hz lamp

HORO 2000 HQI-TS N/L / MHN-LA / MHN-FC



14106003
Aluminium power supply unit IP65, 400 V - 50 Hz, class I, for 2000 W HQI-T / MHN-LA / MHN-FC / HQI-TS N/L metal halide lamps (not for HQI-TS and HQI-TS High Flux), without ignitor

OPTIONAL ACCESSORIES

HORO



14090394
External cowl in sheet aluminium, provides full cut off with peak beam max 55° and reduces upward light pollution.



14090494
External cowl in sheet aluminium, provides full cut off with peak beam max 60° and reduces upward light pollution.



14090594
External cowl in sheet aluminium, provides full cut off with peak beam max 65° and reduces upward light pollution.



14090202
Long mounting bracket in hot dipped galvanised steel suitable for use when mounting one floodlight above another to avoid interference of light distribution.