

## HORO 2000 A/M




<b>Part number</b>	04022094
<b>Lampholder:</b>	cabie
<b>Light Source:</b>	METAL HALIDE LAMPS
<b>Wattage:</b>	1x2000 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP 65
<b>IK-J-xxIP:</b>	IK09 12J xx7
<b>Optic:</b>	ASYMMETRIC MEDIUM REFLECTOR
<b>Ta MIN luminaire:</b>	-30°
<b>Ta MAX luminaire:</b>	25°





### Description

- Discharge lamp floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Flat extra clear tempered glass diffuser
  - Extra pure polished aluminium reflectors
  - Anti-ageing silicone gasket
  - Automatic line isolator switch in LCP
  - Electrical connection box in black technopolymer
  - Ceramic lamp supports with stainless steel check spring
  - Stainless steel locking springs for the glass
  - Stainless steel external screws
  - Fully integrated stainless steel safety spring clips
  - Mounting bracket in hot dip galvanised steel
  - Patented anti-vacuum device
  - Adequate power supply units, available as accessories, must be used for all floodlights

### PHOTOMETRIC DATA



### TECHNICAL DRAWINGS



## CONTROL GEAR

### HORO 2000 HQI-TS D/S / HQI-TS N/L / MHN-LA / MHN-FC



14020601  
Power supply unit 400 V - 50 Hz, class I, on galvanised steel plate for 2000W metal halide lamps (not for HQI-TS and HQI-TS High Flux) with fuse and without ignitor



14014420  
Set including power supply unit and power-factor capacitor for 2000W HQI-TS 400V 50 Hz lamp

### HORO 2000 HQI-TS N/L / MHN-LA / MHN-FC



14106003  
Aluminium power supply unit IP65, 400 V - 50 Hz, class I, for 2000 W HQI-T / MHN-LA / MHN-FC / HQI-TS N/L metal halide lamps (not for HQI-TS and HQI-TS High Flux), without ignitor

## OPTIONAL ACCESSORIES

### HORO



14090394  
External cowl in sheet aluminium, provides full cut off with peak beam max 55° and reduces upward light pollution.



14090494  
External cowl in sheet aluminium, provides full cut off with peak beam max 60° and reduces upward light pollution.



14090594  
External cowl in sheet aluminium, provides full cut off with peak beam max 65° and reduces upward light pollution.



14090202  
Long mounting bracket in hot dipped galvanised steel suitable for use when mounting one floodlight above another to avoid interference of light distribution.



14159204  
Horo viewfinder