

INSERT+ 1/2



INSERT+ 1



INSERT+ 2

- ¬ Series of wall recessed luminaires for indoor and outdoor general lighting use in two sizes,
- ¬ Painted die-cast aluminium housing
- ¬ Diffuser in flat glass, internally frosted
- ¬ Silicone gasket
- \neg External electrical connection with sealed plug-socket QUICK, complete with cable
- ¬ Electrical connector for wires Ø 7 Ø 12 mm
- ¬ LED versions include 220-240 V 50/60 Hz safety transformer
- ¬ Stainless steel locking screws
- ¬ The fixture requires recessed fixing box which must be ordered separately
- ¬ The recessed box is equipped with a removable cover and provided with two spirit levels to facilitate the installation process
- ¬ INSERT+ 1/2 could be installed in exisiting recess boxes of INSERT 1/2 thanks to the dedicated adapter accessory
- ¬ Supplied with 0,2 m pre-wired HORNF-5 cable
- ¬ For the Insert+2 series, connectors for through wiring connections are available as accessories. Connectors fit wires measuring \emptyset 7 - \emptyset 10.5 mm and \emptyset 14 - \emptyset 17 mm

















- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- O WH-87 / White / Textured























The product is provided pre-cabled with brass cable clamp.



The fixture requires recessed fixing box which must be ordered separately.


INSERT+ 1 IK07 2J xx5

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Φ ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	В	LIFETIME	COLOUR/ RAL	PART NUMBER
Power	LED 220	0-240) V 50	0/6	0 Hz										
LED	7 W	1		80	4000		A37/M	-	850 lm	275 lm	80	10	60000 h		304117
LED	7 W	1		80	3000		A37/M	-	825 lm	250 lm	80	10	60000 h		304116
LED	7 W	1		80	4000	•	A37/M	-	850 lm	275 lm	80	10	60000 h		304119
LED	7 W	1		80	3000		A37/M	-	825 lm	250 lm	80	10	60000 h	•	304118
LED	7 W	1		80	4000		A37/M	-	850 lm	275 lm	80	10	60000 h	0	304115
LED	7 W	1		80	3000		A37/M	-	825 lm	250 lm	80	10	60000 h	0	304114



INSERT+ 2 IK07 2J xx5

LAMPHOLDER	WATTAGE	CLASS	W	CRI	KELVIN	COS 0 ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	В	LIFETIME	COLOUR/ RAL	PART NUMBER
Power	LED 22	20-24) V 5	0/6	50 Hz										
LED	10 W	-1		80	4000		A25/W	-	1410 lm	553 lm	80	10	60000 h		304123
LED	10 W	1		80	3000		A25/W	-	1350 lm	503 lm	80	10	60000 h		304122
LED	10 W	1		80	4000		A25/W	-	1410 lm	553 lm	80	10	60000 h	•	304125
LED	10 W	-1		80	3000		A25/W	-	1350 lm	503 lm	80	10	60000 h	•	304124
LED	10 W	1		80	4000		A25/W	-	1410 lm	553 lm	80	10	60000 h	0	304121
LED	10 W	T.		80	3000		A25/W	-	1350 lm	503 lm	80	10	60000 h	0	304120



MANDATORY ACCESSORIES





Complete unit

1A+1B = please order 2 codes

COMPONENTS


A luminaire

B recessed fixing kit

DESCRIPTION	COLOR	PART NUMBER
INSERT+ 1		
Recessed box INSERT+ 1		310475
INSERT+ 2		
Recessed box Insert + 2		310490



310475





310490











Complete unit


1A+1B = please order 2 codes

COMPONENTS


luminaire

adaptor recessed fixing kit

DESCRIPTION	COLOR	PART NUMBER
INSERT+ 1		
Adaptor INSERT+ 1	0	310476
Adaptor INSERT+ 1		310477
Adaptor INSERT+ 1	•	310478
INSERT+ 2		
Adaptor INSERT+ 2	0	310487
Adaptador INSERT+ 2		310488
Adaptor NSERT+ 2	•	310489
Connection Kit Y 3-way D.14-17mm IP68		310495
Connection Kit Y 3-way D.7-10.5mm IP68		310496



310476 - WH1 **310477** - GR3 **310478** - AN3



310487 - WH1 **310488** - GR3 **310489** - AN3



310495 - Ø 14-17 mm **310496** - Ø 7-10,5 mm