

INSERT+ 1 MARINE




Part number	304792
Lampholder:	LED
Light Source:	LED
Wattage:	6 W
Finish:	BR-10 / Natural brass / Glossy
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Asymmetric medium reflector
Lightsource lumen output:	850 lm
Luminaire lumen output:	354 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-10°
Ta MAX luminaire:	35°




Description

- Wall recessed luminaire, for indoor and outdoor comprising:
- Polyester powder coated ISO 9227 die-cast aluminium housing
 - Powder polyester painting process optimized against UV rays in 13 different steps ISO 9227
 - Die cast polished brass ring with vibratory finishing.
 - Metals with natural finish surface may oxidise with age. To restore the original brightness use commercial metal polish
 - Diffuser in flat glass, internally frosted
 - EPDM gasket
 - Stainless steel locking screws
 - Supplied with 0,2 m pre-wired H07RN-F cable
 - External electrical connection with sealed plug-socket QUICK, complete with cable
 - Electrical connector for wires \varnothing 7 - \varnothing 12 mm
 - The fixture requires recessed fixing box which must be ordered separately
 - The recessed box is equipped with a removable cover and provided with two spirit levels to facilitate the installation process
 - LED versions include 220/240 V 50/60 Hz safety transformer
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



MANDATORY ACCESSORIES

INSERT+ 1 MARINE



310475

Recessed box INSERT+ 1