

## INSERT+ 3 A/W



<b>Part number</b>	3100877
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	27 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK10 20J xx9
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Asymmetric wide reflector
<b>Lightsource lumen output:</b>	4020 lm
<b>Luminaire lumen output:</b>	1502 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°




### Description


Wall recessed luminaire, for indoor and outdoor use in solid and hollow walls, for general lighting, comprising:

- Die-cast painted aluminium housing and trim ISO 9227
- Tempered clear glass diffuser
- Diffuser in flat glass, internally frosted
- Silicone gasket
- External electrical connection with sealed plug-socket QUICK, complete with cable
- Electrical connector for wires  $\varnothing$  7 -  $\varnothing$  12 mm
- LED versions include 220/240 V 50/60 Hz safety transformer
- Stainless steel locking screws
- The fixture requires recessed fixing box which must be ordered separately
- Supplied with 0,5 m pre-wired H07RN-F cable
- Anti-tamper kit available as an accessory
- Available for thorough wiring as accessories. Connectors fit  $\varnothing$  7 -  $\varnothing$  10,5 mm and  $\varnothing$  14 -  $\varnothing$  17 mm cables
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings



## MANDATORY ACCESSORIES

### INSERT+3



3100883  
Recessed box INSERT+3  
Stainless steel

## OPTIONAL ACCESSORIES

### INSERT+ 3



3100992  
Stainless steel, anti-tamper locking  
screws



310495  
Connection Kit Y 3-way D.14-17mm  
IP68



310496  
Connection Kit Y 3-way D.7-10.5mm  
IP68