

## LAMA+ MINI S/W




<b>Part number</b>	3101195
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	39 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC WIDE REFLECTOR
<b>Lightsource lumen output:</b>	6048 lm
<b>Luminaire lumen output:</b>	4725 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	45°



### Description

- Suspended LED fixture series for indoors, made up of:
- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
  - Flat extra clear tempered glass diffuser
  - High-transparency polycarbonate lenses for best light transmission
  - Anti-aging silicone gasket with high resiliency
  - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables  $\varnothing$  9 -  $\varnothing$  12 mm
  - Galvanised steel suspension hooks
  - Stainless steel external screws
  - Stainless steel locking springs for the glass
  - EM versions are complete with emergency device that can operate on battery for 1 hour.
- Product can be used for general or emergency lighting.
- Versions are available with ON-OFF driver and dimmable DALI
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

