

## LM4 S/EW




<b>Part number</b>	3101705
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	72 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK06 0.80J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	12204 lm
<b>Luminaire lumen output:</b>	9464 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-40°
<b>Ta MAX luminaire:</b>	40°



### Description

- Range of indoor and outdoor LED fixtures, comprising:
- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
  - Diffuser made of extra clear, flat glass, tempered, markings with serigraphy, internally ice etched
  - Anti-aging silicone gasket with high resiliency
  - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables  $\varnothing 9 - \varnothing 12$  mm
  - Stainless steel external screws
  - Stainless steel locking springs for the glass
  - Stainless steel springs for quick ceiling mount
  - 3000 K and 5000 K available upon request
  - EM versions are complete with emergency device that can operate on battery for 1 hour.
- Product can be used for general or emergency lighting.
- Versions are available with ON-OFF driver and dimmable DALI
  - Through-wiring version available upon request
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

