


LYRA+




Scan the QR-code for the latest information

■ AN-96 / Anthracite gray / Textured


LED street luminaire, comprising:

- Die-cast aluminium housing and cover, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Die-cast aluminium pole clamp with polyester powder coat finish ISO 9227/19244 - ISO 9233 (C5) , for Ø 60 mm poles
- High-transparency polycarbonate optics
- Anti-ageing custom moulded silicone sealing gasket(s) with resilient elastic return capacity
- Extra clear, toughened, flat glass diffuser
- Stainless steel fasteners for glass
- Built-in driver
- Supplementary device for protection against network surges of up to 10 kV (DM) included
- Stainless steel locking hardware
- Complete with 1 m factory pre-wired cable H07RN-F 2x1.5 mm²
- Pole clamp for Ø 76 mm poles is available as accessory
- UNI 10819 light pollution standards compliant (0% ULOR rating)
- On request, the appliances can be supplied with SR/075 optics for narrow roads and with W/H ratio (road width/pole height) up to 0.75, SR/125 for wide roads and with W/H ratio of 1.25 and SR/150 wide roads and with W/H ratio of 1.5
- Contact the company for DALI dimming versions or with ZHAGA socket and D4i driver
- CLO (Constant Light Output) options available. Consult factory
- Design by GIORGIO LODI
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08



LYRA+

Identifying and classifying our optics



LYRA+ SR/100

IP66 - IK06



LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED - with automatic power reduction 220-240 V 50/60 Hz										
65	II	-	70	4000	SR/100	100°	9800	9365	■	3115301
65	II	-	70	3000	SR/100	100°	9320	8513	■	3115300
54	II	-	70	4000	SR/100	100°	8680	7669	■	3115299
54	II	-	70	3000	SR/100	100°	7200	6970	■	3115298
30	II	-	70	4000	SR/100	100°	4480	3939	■	3115297
30	II	-	70	3000	SR/100	100°	3560	3580	■	3115296
20	II	-	70	4000	SR/100	100°	3740	2820	■	3116039
20	II	-	70	3000	SR/100	100°	3560	2560	■	3116038

Optional accessories

DESCRIPTION	COLOR	PART NUMBER
LYRA+		
Painted die-cast aluminium pole-mounting joint for pole Ø 76 mm	■	3117338
Hot-dipped galvanized wall angled steel bracket, cataphoresis and polyester powder	■	1407796



3117338



1407796