


MIMIK 10 FLAT M



Part number	304826
Lampholder:	LED
Light Source:	LED
Wattage:	5 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric wide reflector
Lightsource lumen output:	700 lm
Luminaire lumen output:	487 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°
ULR:	0%




Description


Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Anti-ageing silicone gasket
- Built-in driver
- Stainless steel looking grains
- Single (M) and dual (B) emission versions
- The MIMIK versions are available with asymmetric (CP) beam lenses, or with narrow beam (C/I) circular lenses. In the twin emission versions (B), the two different beam types can be combined (CP+C/I, C/I+C/I).
- "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK 10 - FLAT M



310919

Customising ring / Facade Accessory

Anthracite gray