


# MIMIK 20 CEILING




<b>Part number</b>	3105855
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	23.5 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Symmetric extra wide reflector
<b>Lightsource lumen output:</b>	3560 lm
<b>Luminaire lumen output:</b>	1778 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	84000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	40°
<b>ULR:</b>	0%



## Description

- Ceiling surface mounted LED luminaire, comprising:
- Die-cast aluminium housing, powder-polyester coated ISO 9227
  - Glass diffuser, internally painted for homogeneous diffused light
  - Anti-ageing silicone gasket
  - Built-in driver
  - Available with ON-OFF driver and dimmable DALI
  - Stainless steel looking grains
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

