


## MIMIK 50 M CP/T2



<b>Part number</b>	3104485
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	39 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Pedestrian and cycle reflector type 2
<b>Lightsource lumen output:</b>	6920 lm
<b>Luminaire lumen output:</b>	4870 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	71000 h
<b>Ta MIN luminaire:</b>	-25°
<b>Ta MAX luminaire:</b>	45°
<b>ULR:</b>	0%




### Description

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Anti-ageing silicone gasket
- Extra-clear, tempered, flat glass diffuser, screen-printed inside
- 3000 K and 4000 K, multichip LED board
- High-transparency polycarbonate lenses grant an optimized light transmission
- Built-in driver
- Stainless steel looking grains
- EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
- Ni-Cd 3,6 V, 4 Ah batteries, 24 hours recharge time
- Single (M) and dual (B) emission versions
- Double emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
- Double emission (B) DALI versions have two drivers. Dual ignition is possible by assigning and managing addresses within the DALI protocol
- DALI versions have an ambient operating temperature up to -40°C
- "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

