


MIMIK 50 M CP/T2 EM3P



Part number	3104493
Lampholder:	LED
Light Source:	LED
Wattage:	39 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
Optic:	Pedestrian and cycle reflector type 2
Lightsource lumen output:	6920 lm
Luminaire lumen output:	4870 lm
L:	L80
B:	B10
Lifetime:	71000 h
Ta MIN luminaire:	0°
Ta MAX luminaire:	35°
ULR:	0%



Description

Photometric data

Technical drawings

Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Anti-ageing silicone gasket
- Extra-clear, tempered, flat glass diffuser, screen-printed inside
- 3000 K and 4000 K, multichip LED board
- High-transparency polycarbonate lenses grant an optimized light transmission
- Built-in driver
- Stainless steel looking grains
- EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
- Ni-Cd 3,6 V, 4 Ah batteries, 24 hours recharge time
- Single (M) and dual (B) emission versions
- Double emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
- Double emission (B) DALI versions have two drivers. Dual ignition is possible by assigning and managing addresses within the DALI protocol
- DALI versions have an ambient operating temperature up to -40°C
- "CP" versions feature asymmetric light distribution suitable for bicycle and pedestrian pathways
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

