


## MIMIK 10 CEILING TECH




<b>Part number</b>	304881
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	10 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	70
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	EXTRA WIDE CIRCLE REFLECTOR
<b>Lightsource lumen output:</b>	1120 lm
<b>Luminaire lumen output:</b>	806 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	25°
<b>ULR:</b>	0%



### Description

- Wall and ceiling mounted LED luminaire for indoor and outdoor applications, comprising:
- Polyester powder coated die-cast aluminium housing
  - Flat, microprismatic tempered glass diffuser, screen-printed on the inner surface
  - Silicone gasket
  - Powder polyester painting process optimized against UV rays in 13 different steps
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

