


MIMIK 20 FLAT M



Part number	303842
Lampholder:	LED
Light Source:	LED
Wattage:	13,5 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric wide reflector
Lightsource lumen output:	1653 lm
Luminaire lumen output:	960 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	45°
ULR:	0%




Description


Wall-mounted LED luminaire, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Microprismatic, tempered, flat glass diffuser, screen-printed inside for the MIMIK FLAT versions
- Anti-ageing silicone gasket
- Built-in driver
- MIMIK luminaires are equipped with high-transmittance polycarbonate lenses with different light distributions to meet the most diverse lighting requirements
- M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

MIMIK FLAT M



310450
FLAT M Customising ring / Facade
Accessory

White
