

## NORMA+ PRO 120 CL



|                                  |                                  |
|----------------------------------|----------------------------------|
| <b>Part number</b>               | 3109344                          |
| <b>Lampholder:</b>               | LED                              |
| <b>Light Source:</b>             | LED                              |
| <b>Wattage:</b>                  | 41 W                             |
| <b>Finish:</b>                   | GR-RAL7035 / Grey RAL7035 / Matt |
| <b>Insulation class:</b>         | I                                |
| <b>Degree of protection:</b>     | IP65                             |
| <b>IK-J-xxIP:</b>                | IK09 15J xx7                     |
| <b>CRI:</b>                      | 80                               |
| <b>Kelvin:</b>                   | 4000                             |
| <b>Power factor:</b>             | $\text{COS}\phi \geq 0,9$        |
| <b>Optic:</b>                    | Symmetric extra wide reflector   |
| <b>Lightsource lumen output:</b> | 6795 lm                          |
| <b>Luminaire lumen output:</b>   | 5819 lm                          |
| <b>L:</b>                        | L80                              |
| <b>B:</b>                        | B50                              |
| <b>Lifetime:</b>                 | 80000 h                          |
| <b>Ta MIN luminaire:</b>         | -20°                             |
| <b>Ta MAX luminaire:</b>         | 45°                              |




### Description

Weatherproof LED luminaire, comprising:

- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
- Technopolymers end caps
- Anti-ageing silicone gasket
- Tool-less bayonet opening polycarbonate cap for power connection
- The CL (Continuous Line) versions are suitable for through wiring continuous line installations (5x2,5 mm<sup>2</sup>)
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Aluminium heat sink
- Stainless steel springs for quick installation
- Real lumen output led source with an effective >140 lm/W
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

