


ORION H M




Part number	3105449
Lampholder:	LED
Light Source:	LED
Wattage:	5,5 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric extra wide reflector
Lightsource lumen output:	742 lm
Luminaire lumen output:	259 lm
L:	L70
B:	B10
Lifetime:	35000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°
ULR:	0%




Description

- Wall-mounted LED luminaire, comprising:
- Painted, die-cast aluminium housing, in compact size
 - Microprismatic, flat glass diffuser, screen-printed inside
 - Aluminium reflector
 - Anti-ageing silicone gasket
 - Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Stainless steel looking grains
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings




OPTIONAL ACCESSORIES

ORION




3106290
Carter ORION H

Black



3106289
Carter ORION H

White



3106291
Carter ORION H

Rust