


GUELL 1 C/I




Part number	06288594
Lampholder:	LED
Light Source:	LED
Wattage:	39 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP 66
IK-J-xxIP:	IK07 3J xx5
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	INTENSIVE CIRCLE REFLECTOR
Lightsource lumen output:	5558 lm
Luminaire lumen output:	4599 lm
L:	L70
B:	B10
Lifetime:	150000 h




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminum housing chemically pre-treated and painted with polyester powder coating
 - Flat tempered glass diffuser
 - Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Intensive circular optic
 - Anti-ageing silicone gasket
 - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
 - Stainless steel external screws
 - Fully integrated stainless steel aluminium spring clips
 - Powder coated steel bracket
 - On request, versions with dimmable ballast available
 - 3000 K and 5000 K available upon request

PHOTOMETRIC DATA




TECHNICAL DRAWINGS



OPTIONAL ACCESSORIES

GUELL 1



14172902
Protective grid GUELL 1



14174220
Connection box IP 66




14173394
Wall support 500 mm/19.69" GUELL
1/2

Metallic grey




14173494
Wall support 1000 mm/39.37" GUELL
1/2

Metallic grey



14453194
Single pole top support GUELL 1


Metallic grey



14453294
Double pole top support GUELL 1

Metallic grey

GUELL 1 C/I



14476594
GUELL 1 C/I frosted glass.

Metallic grey