



## Q-LIGHT



<b>Part number</b>	306670
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	14 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK05 0.70J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Symmetric wide reflector
<b>Lightsource lumen output:</b>	1944 lm
<b>Luminaire lumen output:</b>	1024 lm
<b>L:</b>	L90
<b>B:</b>	B10
<b>Lifetime:</b>	36000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°




### Description


Landscaping LED bollard, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Extra pure polished aluminium reflector
- Clear UV-stabilised and impact-resistant technopolymer diffuser
- Die-cast aluminium housing and fixing plate for in-ground installation, painted
- Die-cast aluminium housing complete with two PG11 cable glands suitable for through wiring of  $\varnothing$  5 mm to  $\varnothing$  10 mm cables
- Stainless steel fixing screws and rods
- Extruded aluminium pole powder-polyester coated ISO 9227
- Base plate included
- QUICK versions are supplied complete with IP rated connection box suitable for through wiring for  $\varnothing$  5 mm to  $\varnothing$  13 mm cables
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### Q-LIGHT



310398  
Baseplate Q-series