


Q-LIGHT



Part number	306671
Lampholder:	LED
Light Source:	LED
Wattage:	14 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric wide reflector
Lightsource lumen output:	2088 lm
Luminaire lumen output:	1151 lm
L:	L90
B:	B10
Lifetime:	36000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°




Description


Landscaping LED bollard, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Extra pure polished aluminium reflector
- Clear UV-stabilised and impact-resistant technopolymer diffuser
- Die-cast aluminium housing and fixing plate for in-ground installation, painted
- Die-cast aluminium housing complete with two PG11 cable glands suitable for through wiring of $\varnothing 5$ mm to $\varnothing 10$ mm cables
- Stainless steel fixing screws and rods
- Extruded aluminium pole powder-polyester coated ISO 9227
- Base plate included
- QUICK versions are supplied complete with IP rated connection box suitable for through wiring for $\varnothing 5$ mm to $\varnothing 13$ mm cables
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

Q-LIGHT



310398
Baseplate Q-series