

## QUASAR 60 M




<b>Part number</b>	3100823
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	19 W
<b>Finish:</b>	WH-87 / White / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK06 1J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	Asymmetric extra wide reflector
<b>Lightsource lumen output:</b>	2736 lm
<b>Luminaire lumen output:</b>	1655 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	130000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	45°
<b>ULR:</b>	0%



### Description

- Range of indoor and outdoor wall mounted LED fixtures, comprising:
- Die-cast painted aluminium housing
  - Glass diffuser, internally painted for homogeneous diffused light
  - Flat microprismatic glass diffuser internally pattern for TECH versions
  - Reflector in satin finish pure aluminium (Al 99.98)
  - Silicone gasket
  - EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
  - EM/3P versions are meant to be wired on a branch from the LED board working as both general and emergency lighting.
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings

