

QUASAR 30 CEILING

design by R. FIORATO - F. PAGLIARINI




Range of indoor and outdoor LED fixtures, comprising:
 → Die-cast painted aluminium housing
 → Flat microprismatic glass diffuser internally pattern for TECH versions

- Reflector in satin finish pure aluminium (Al 99.98)
- Silicone gasket
- High frequency electronic ballast supplied as standard



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured



Please visit our web site
www.performanceinlighting.com
 for the latest updated versions available.

QUASAR 30 CEILING TECH

IK07 2J xx5

WATTAGE	CLASS	✓	CRI	KELVIN	COS φ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHT SOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz														
23 W	I	✓	80	4000	✓	S/I	-	2384 lm	1652 lm	80	10	50000 h	●	306177
23 W	I	✓	80	3000	✓	S/I	-	2276 lm	1482 lm	80	10	50000 h	●	306178
23 W	I	✓	80	4000	✓	S/I	-	2384 lm	1652 lm	80	10	50000 h	●	306175
23 W	I	✓	80	3000	✓	S/I	-	2276 lm	1482 lm	80	10	50000 h	●	306176
23 W	I	✓	80	4000	✓	S/I	-	2384 lm	1652 lm	80	10	50000 h	○	306174
23 W	I	✓	80	3000	✓	S/I	-	2276 lm	1482 lm	80	10	50000 h	○	306131

