

# QUASAR 30 CEILING TECH




<b>Part number</b>	306176
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	23 W
<b>Finish:</b>	AN-96 / Anthracite gray / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP65
<b>IK-J-xxIP:</b>	IK07 2J xx5
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>Optic:</b>	SYMMETRIC NARROW REFLECTOR
<b>Lightsource lumen output:</b>	2276 lm
<b>Luminaire lumen output:</b>	1482 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	35°
<b>ULR:</b>	0%



## Description

- Indoor and outdoor luminaire, comprising:
- Die-cast painted aluminium housing
  - Flat microprismatic glass diffuser internally pattern for TECH versions
  - Reflector in satin finish pure aluminium (Al 99.98)
  - Silicone gasket
  - High frequency electronic ballast supplied as standard
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

## Photometric data



## Technical drawings

