

# QUASAR 10 CEILING

design by R. FIORATO - F. PAGLIARINI



Range of indoor and outdoor LED fixtures, comprising:


- Die-cast painted aluminium housing
- Diffuser in flat glass, internally frosted
- Polymer gasket
- Stainless steel fastening screws and dowels
- Built-in driver



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured



Please visit our web site  
[www.performanceinlighting.com](http://www.performanceinlighting.com)  
 for the latest updated versions available.



## QUASAR 10 CEILING

IK06 1J xx3

WATTAGE	CLASS	CFR	KELVIN	COS φ ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 230 V 50 Hz</b>													
5 W	I	-	80	4000	✓	S/EW	-	500 lm	255 lm	70	10	60000 h	● 304488
5 W	I	-	80	3000	✓	S/EW	-	500 lm	221 lm	70	10	60000 h	● 304487
5 W	I	-	80	4000	✓	S/EW	-	500 lm	255 lm	70	10	60000 h	● 304490
5 W	I	-	80	3000	✓	S/EW	-	500 lm	221 lm	70	10	60000 h	● 304489
5 W	I	-	80	4000	✓	S/EW	-	500 lm	255 lm	70	10	60000 h	○ 304492
5 W	I	-	80	3000	✓	S/EW	-	500 lm	221 lm	70	10	60000 h	○ 304491

