

SL764AB LED OPAL COVER HIGH




Part number	8764651406370
Lampholder:	LED
Light Source:	LED
Wattage:	42 W
Finish:	GR-EV1 / Anodised grey / Matt
Insulation class:	I
Degree of protection:	IP30
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	3000
Power factor:	COS ϕ \geq 0,9
EEL:	A1
Optic:	Symmetric Direct lighting
Optic Beam:	2 x 81°/49°
Lightsource lumen output:	5290 lm
Luminaire lumen output:	4440 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°



Description

- LED surface-mount luminaire for interior, comprising:
- Extruded aluminium housing, anodised (EV1), die-cast aluminium endcaps, powder painted
 - Opal PMMA diffuser for optimal light diffusion and a high light uniformity
 - Direct light distribution
 - Colour rendering index Ra > 80
 - Colour tolerance according to MacAdam \leq 3 SDCM
 - Dimmable via TouchDIM®
 - Interchangeable lighting inserts
 - Flexible choice of feed points
 - DALI dimmable
 - Special colour versions available upon request
 - Continuous mounted version at www.light-performer.com

Photometric data



Technical drawings

