


SL787+ PL OP




Part number	3109605
Lampholder:	LED
Wattage:	10 W
Finish:	GR-EV1 / Anodised grey / Matt
Insulation class:	I
Degree of protection:	IP30
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	3000
Power factor:	$\text{COS}\phi \geq 0,9$
EEL:	A2
Optic:	Symmetric direct lighting
Optic Beam:	2 x 48°/51°
Lightsource lumen output:	1630 lm
Luminaire lumen output:	1450 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°



Description

- Suspended, LED luminaire for indoor, comprising:
- Extruded anodised aluminium housing
 - Die-cast aluminium end caps, painted
 - Opal PMMA diffuser for optimal light diffusion and uniformity
 - Streamlined, simple design with flush end caps
 - High-quality workmanship of profile connections for a perfect look
 - High economic efficiency thanks to luminaire efficiencies of up to 159 lm/W
 - UGR <19 for all luminosities
 - Through-wiring designed
 - Simple and convenient lighting installation
 - Interchangeable lighting inserts
 - Direct light distribution
 - Colour rendering index $R_a > 80$
 - Colour tolerance according to MacAdam ≤ 3 SDCM
 - Complete with steel suspension cable (1.5 m), transparent power cable and canopy
 - Many other luminaire designs and strip light configurations are available at www.light-performer.com

Photometric data



Technical drawings

