


## SL787+ PL OP




<b>Part number</b>	3109607
<b>Lampholder:</b>	LED
<b>Wattage:</b>	12 W
<b>Finish:</b>	GR-EV1 / Anodised grey / Matt
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP30
<b>IK-J-xxIP:</b>	IK05 0.70J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>EEL:</b>	A2
<b>Optic:</b>	Symmetric direct lighting
<b>Optic Beam:</b>	$2 \times 48^\circ/51^\circ$
<b>Lightsource lumen output:</b>	2040 lm
<b>Luminaire lumen output:</b>	1820 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	10°
<b>Ta MAX luminaire:</b>	40°



### Description

- Suspended, LED luminaire for indoor, comprising:
- Extruded anodised aluminium housing
  - Die-cast aluminium end caps, painted
  - Opal PMMA diffuser for optimal light diffusion and uniformity
  - Streamlined, simple design with flush end caps
  - High-quality workmanship of profile connections for a perfect look
  - High economic efficiency thanks to luminaire efficiencies of up to 159 lm/W
  - UGR <19 for all luminosities
  - Through-wiring designed
  - Simple and convenient lighting installation
  - Interchangeable lighting inserts
  - Direct light distribution
  - Colour rendering index  $R_a > 80$
  - Colour tolerance according to MacAdam  $\leq 3$  SDCM
  - Complete with steel suspension cable (1.5 m), transparent power cable and canopy
  - Many other luminaire designs and strip light configurations are available at [www.lightperformer.com](http://www.lightperformer.com)

### Photometric data



### Technical drawings

