

## SPIDER+ 20 A/EW




<b>Part number</b>	3106053
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	37/51 W
<b>Finish:</b>	BK-81 / Black / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP67
<b>IK-J-xxIP:</b>	IK05 0.8J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	3000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	Asymmetric extra wide reflector
<b>Lightsource lumen output:</b>	6677 lm
<b>Luminaire lumen output:</b>	5754 lm
<b>L:</b>	L70
<b>B:</b>	B10
<b>Lifetime:</b>	70000 h
<b>Ta MIN luminaire:</b>	-20°
<b>Ta MAX luminaire:</b>	30°
<b>ULR:</b>	0%
<b>IPEA* (Street Lighting):</b>	A4+
<b>IPEA* (Area Lighting):</b>	A5+
<b>IPEA* (Cycle/Pedestrian Lighting):</b>	A4+
<b>IPEA* (Green Areas):</b>	A4+
<b>IPEA* (Historical Areas):</b>	A7+
<b>Luminous Intensity Class:</b>	G*6




### Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
  - Extra-clear flat tempered glass diffuser internally screen-printed
  - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
  - Extra pure polished aluminium reflectors
  - Asymmetrical optic
  - Anti-ageing silicone gasket
  - Electrical connection through an IP68 quick external socket-plug connector that makes it possible to connect it to the network without opening the lighting element, made of techno-polymer, 3 poles x 1.5/2.5 mm<sup>2</sup>, for wires  $\phi$  8 -  $\phi$  12 mm
  - Luminaire designed to operate with two predetermined power levels that can be selected by the user with the external button
  - Stainless steel external screws
  - Cataphoretic process polyester powder-coated steel bracket with simplified mounting system
  - Complete with magnetic level to be placed on the bracket at the time of mounting
  - The luminous flux data shown refers to the maximum power
  - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings







14174220  
Connection box IP 66