

STRIP SQUARE+ INGROUND 1300



Part number	3109379
Lampholder:	LED
Light source:	LED
Wattage:	33 W
Finishing:	GR-11 / Anodised grey / Matt
Insulation class:	I
IP degree of protection:	IP67
IK-J-xxIP:	IK10 20J xx9
CRI:	80
Colour temperature:	3000
Power factor / COS Φ:	>0.9
Lightsource lumen output (lm):	5000 lm
Luminaire lumen output (lm):	3324 lm
L:	L80
B:	B10
Lifetime:	60000 h
Ingrounds classification:	A1 A2 A3 A4 A5
Glass temperature (°C):	35
Min. ambient temperature (°C):	-25
Max. ambient temperature (°C):	45




Description


Recessed inground luminaire for interior and exterior use comprising:

- Extruded anodised aluminium housing
- Tempered glass diffuser, screen-printed inside
- Die-cast aluminium end caps, painted
- Anti-ageing silicone gasket
- QUICK versions are supplied complete with IP rated connection box suitable for through wiring for Ø 5 mm to Ø 13 mm cables
- Stainless steel locking screws
- Aluminium gear tray for high heat dissipation of components
- Built-in driver
- Recessed box to be ordered separately
- Through-wiring designed
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



MANDATORY ACCESSORIES

STRIP SQUARE+ INGROUND



310425
Recessed fixing kit L 1346 mm

