

STRIP SQUARE+ INGROUND 800




Part number	3109363
Lampholder:	LED
Light source:	LED
Wattage:	20.5 W
Finish:	GR-11 / Anodised grey / Matt
Insulation class:	I
Degree of protection:	IP67
IK-J-xxIP:	IK10 20J xx9
CRI:	80
Kelvin:	3000
Power factor / COS Φ:	>0.9
Lightsource lumen output:	3000 lm
Luminaire lumen output:	2001 lm
L:	L80
B:	B10
Lifetime:	60000 h
Classification of recessed luminaires:	A1 A2 A3 A4 A5
Glass temperature (°C):	35
Ta MIN luminaire (°C):	-25
Ta MAX luminaire (°C):	45




Description

- Recessed inground luminaire for interior and exterior use comprising:
- Extruded anodised aluminium housing
 - Tempered glass diffuser, screen-printed inside
 - Die-cast aluminium end caps, painted
 - Anti-ageing silicone gasket
 - QUICK versions are supplied complete with IP rated connection box suitable for through wiring for Ø 5 mm to Ø 13 mm cables
 - Stainless steel locking screws
 - Aluminium gear tray for high heat dissipation of components
 - Built-in driver
 - Recessed box to be ordered separately
 - Through-wiring designed
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data




Technical drawings



MANDATORY ACCESSORIES

STRIP SQUARE+ INGROUND



310423
Recessed fixing kit L 842 mm

