



light source

work equipment  
connected load  
Power consumption  
luminous flux  
luminous efficacy  
colour temperature  
color rendering index (CRI)  
chromaticity tolerance LED  
System of protection  
class of protection  
operation  
luminaire body

lamp cover  
tubular sections

balance of articulation joints  
weight (net)  
mains lead

## Fastening

## special features

LED

Energy efficiency category A/A+/A++  
electronic plug-in transformer  
100-240 V; 50/60 Hz  
approx. 14 W  
approx. 600 lm  
approx. 42 lm/W  
neutral white, approx. 5000 K  
≥ 80  
4 SDCM  
IP20  
II  
multi-function switch  
sectional aluminium, anodised, aluminium coloured  
anodised  
polycarbonate, white opal  
tubular aluminium section, anodized, aluminium coloured  
anodised  
spring  
approx. 1.5 kg  
approx. 3 m; mains plug  
BS 1363  
CEE 7/XVI  
NEMA 1-15P  
screw-down flange, table clamp (accessory), wall bracket  
(accessory)  
Ra (luminaire) ca. 90



BS 1363



CEE 7/XVI




NEMA 1-15P

**illuminance**

distance: 50 cm

**Em:** 361 lx  
**E<sub>max</sub>:** 816 lx  
**E<sub>min</sub>:** 105 lx



**luminous intensity**

