

TYK+ 20 C/I




Part number	3107328
Lampholder:	LED
Light Source:	LED
Wattage:	50 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	II
Degree of protection:	IP66
IK-J-xxIP:	IK07 4J xx5
CRI:	80
Kelvin:	4000
Power factor:	COSφ ≥ 0,9
Optic:	Intensive circle reflector
Optic Beam:	10°
Lightsource lumen output:	5880 lm
Luminaire lumen output:	4593 lm
L:	L90
B:	B10
Lifetime:	75000 h
Glass temperature:	58°
Ta MIN luminaire:	-40°
Ta MAX luminaire:	50°
ULR:	0%




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Luminaire designed with two separate die-cast aluminium compartments to maximise heat dissipation between electronic components and the LEDs, powder-polyester coated ISO 9227
 - Extra-clear, tempered, flat glass diffuser, screen-printed inside
 - Diffuser permanently sealed to the housing through a high-temperature resistant silicone
 - High-transparency polycarbonate lenses grant an optimized light transmission
 - Intensive circular optic
 - High resiliency anti-ageing silicone gasket with high elastic return capacity
 - Tear-proof nickelled brass cable gland M20x1.5 for cables Ø 10 mm- Ø 14 mm
 - Drivers with surge protection up to 6 kV (DM)
 - Stainless steel external screws
 - Stainless steel wall-mounting bracket
 - Graduated goniometer for aiming purposes made in stainless steel
 - The snoot accessory is compatible with versions that have C/I narrow-beam lenses
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings




OPTIONAL ACCESSORIES

TYK+ 20 C/I



3107466
Anti-glare snoot
Black

TYK+ 20



3107473
Two-axis rotation bracket for gliding support
Stainless steel



3108557
Extra rotation bracket +55°/-90°
Stainless steel




14099896
Gliding support made of painted aluminium for the installation on Ø 60 mm posts
Anthracite gray



14099696
Gliding support made of painted aluminium for the installation on Ø 90 mm posts
Anthracite gray



14029094
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 1 luminaire
Metallic grey



14047194
Gliding support made of painted aluminium for the installation on 60-76 mm Ø posts. 2 opposed luminaires
Metallic grey