

# WL390 OPAL




<b>Part number</b>	3105560
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	38 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	II
<b>Degree of protection:</b>	IP20
<b>IK-J-xxIP:</b>	IK05 0.70J xx3
<b>CRI:</b>	80
<b>Kelvin:</b>	4000
<b>Power factor:</b>	$\text{COS}\phi \geq 0,9$
<b>EEL:</b>	A1
<b>Optic:</b>	Symmetric direct lighting
<b>Lightsource lumen output:</b>	5000 lm
<b>Luminaire lumen output:</b>	4020 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	50000 h
<b>Ta MIN luminaire:</b>	10°
<b>Ta MAX luminaire:</b>	40°



## Description

- Wall and ceiling mounted LED luminaire for indoors, comprising:
- technopolymer housing
  - Light orienting technopolymer optic for a homogenous light distribution over the entire area of the cover
  - Direct light distribution
  - Light colour can be selected between 3000K and 4000K
  - Two power levels can be set via a switch
  - Colour rendering index  $R_a > 80$
  - Colour tolerance according to MacAdam  $\leq 3$  SDCM
  - Complete with electric converter
  - Through wiring

## Photometric data



## Technical drawings

