



Terminal max.:  
~240V / 10A  
0,75 - 2,5 mm<sup>2</sup>




THIS PRODUCT CONTAINS LIGHT SOURCES  
OF ENERGY EFFICIENCY CLASS:









	3000 K	4000 K	2700-6500 K
CRI 80	E	E	-

**IMPORTANT NOTE:**  
Before performing any exchange please contact  
[ecodesignsupport.de@pil.lighting](mailto:ecodesignsupport.de@pil.lighting)  
for technical instructions.

Modell	Voltage	Wattage	CCT	L (mm)	W (mm)	H (mm)
WL RECT 900	220V - 240V	24W / 31W	3000K / 4000K	900	130	55
WL RECT 1200	220V - 240V	28W / 37W	3000K / 4000K	1200	130	55
WL RECT 1500	220V - 240V	27W / 36W / 48W	3000K / 4000K	1500	130	55



IEC/EN60598-1 IEC/EN60598-2-1 EN62471:2008 EN55015 EN61547 EN61000-3-1 EN61000-3-2



# Montageanleitung

- Folgen Sie dieser Montageanleitung um die korrekte Installation der Leuchte sicherzustellen.
- Bewahren Sie die Anleitung für zukünftige Fragen auf. Alle Arbeiten an dem Produkt sind im spannungsfreien Zustand durchzuführen.
- Der elektrische Anschluss ist nur von einer qualifizierten Elektrofachkraft durchzuführen.

# Installation instruction

- Always follow this instruction to ensure correct and safe installation and functioning of the luminaire and keep it for future reference.
- Always isolate the power before commencing installation.
- If in doubt, consult a qualified electrician. Ensure that you always install the luminaire to the relevant regulations.