

WL RECT





Scan the QR-code for the latest information

WH-87 / White / Textured

LED surface-mount luminaire for indoor, comprising:

- Technopolymer housing
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Two power levels can be set via a switch
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through wiring
- Built-in driver



 max 0,9 kg

WL
900 OPAL

 max 1,5 kg

WL
1200 OPAL

 max 2,8 kg

WL
1500 OPAL

WL900 OPAL

IP20 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
24/31	II	-	80	3000/4000	S/B	2 x 62°/58°	4700	3050	<input type="checkbox"/>	3118547
Power LED - dimmable DALI 220-240 V 50/60 Hz										
31	II	-	80	3000/4000	S/B	2 x 62°/58°	4700	3780	<input type="checkbox"/>	3118559

WL1200 OPAL

IP20 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
28/37	II	-	80	3000/4000	S/B	2 x 62°/58°	5850	4680	<input type="checkbox"/>	3118548
Power LED - dimmable DALI 220-240 V 50/60 Hz										
28	II	-	80	3000/4000	S/B	2 x 62°/58°	5850	4680	<input type="checkbox"/>	3118560

WL1500 OPAL

IP20 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
27/36/48	II	-	80	3000/4000	S/B	2 x 62°/58°	7200	5760	<input type="checkbox"/>	3118549
Power LED - dimmable DALI 220-240 V 50/60 Hz										
48	II	-	80	3000/4000	S/B	2 x 62°/58°	7200	5760	<input type="checkbox"/>	3118561

