



YPSILON+ A/W




Part number	3105378
Lampholder:	LED
Light Source:	LED
Wattage:	35 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1J xx3
CRI:	70
Kelvin:	3000
Power factor:	COS ϕ \geq 0,9
Optic:	Asymmetric Wide Reflector
Lightsource lumen output:	5291 lm
Luminaire lumen output:	4991 lm
L:	L80
B:	B10
Lifetime:	100000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°
ULR:	0%
IPEA* (Street Lighting):	A9+
IPEA* (Area Lighting):	A9+
IPEA* (Cycle/Pedestrian Lighting):	A8+
IPEA* (Green Areas):	A8+
IPEA* (Historical Areas):	A12+
Luminous Intensity Class:	G*6



Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Flat extra clear tempered glass diffuser
 - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
 - High-transparency polycarbonate lenses for best light transmission
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - Powder coated steel bracket
 - Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
 - Consult factory for other colour temperatures and colour rendering index
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

