

Luminaire with a higher protection rating - Diffuser, opal - direct distribution - impact-resistant

Housing with a smooth surface made of polycarbonate. Cable entry on front with twist-fix bayonet closure; with click-lock catch on the side. Housing colour light grey; Diffuser, opal. Integrated driver. Electrical connection via 3-pole connection terminal with plug-in contacts. Sensor Anbau-Set, ist separat zu bestellen.

## CHARACTERISTICS

Order number	50115024100
EAN-number	4020863374489
Commodity code	94051040
Certification mark	IP 65, Protection class I, F, D, DIN10500/Food/IFS, Indoor, CE
Impact resistance (IK rating)	IK08 (-20°C bis 45°C)
Ambient temperatur	ta -20°C to 45°C

## ELECTRICAL ENGINEERING

Operating device	Electronic driver (1 pcs.)
System output	50 W
Mains voltage	230 V / 50 Hz
Energy efficiency class	A++
Energy efficiency class CELMA EEI	-

## LIGHTING TECHNOLOGY


Configuration	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Luminaire luminous flux	7142 lm
LED service life	50000h L80/B10 (Tq 45°C)
Luminaire luminous efficacy	144 lm/W

## MECHANICS

Colour of the housing	light grey
Dimensions LxWxH/DxH	1500 x 87 x 66 mm
Weight (net)	1.8 kg
Cable entry KE X/Y	0 mm / 750 mm
Mounting method	Surface single mounting, Suspended single mounting, Wall surface-mounting, Mounting rail mounting

## DEEP-LINK

<https://www.regiolum.de/en/article/50115024100>



Configuration	LED 7100 840
ηLB	100 %
Φ ↓/↑	92 % / 8 %
UGR lat./long.	25.8 / 23.7

