

Luminaire with a higher protection rating - Diffuser, opal - direct distribution - impact-resistant, durchgangsverdrahtet  
Housing with a smooth surface made of polycarbonate. Cable entry on front with twist-fix bayonet closure; with click-lock catch on the side.  
Housing colour light grey; Diffuser, opal. Integrated driver. Electrical connection via 3-pole connection terminal with plug-in contacts.  
Through-wiring. Sensor Anbau-Set, ist separat zu bestellen.

## CHARACTERISTICS

Order number	50122014100
EAN-number	4020863381449
Commodity code	94051040
Certification mark	IP 65, Protection class I, F, D, DIN10500/Food/IFS, Indoor, CE
Impact resistance (IK rating)	IK08 (-20°C bis 45°C)
Ambient temperatur	ta -20°C to 45°C

## ELECTRICAL ENGINEERING

Operating device	Electronic driver (1 pcs.)
System output	28 W
Mains voltage	230 V / 50 Hz
Energy efficiency class	A++
Energy efficiency class CELMA EEI	-

## LIGHTING TECHNOLOGY


Configuration	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Luminaire luminous flux	4128 lm
LED service life	50000h L80/B10 (Tq 45°C)
Luminaire luminous efficacy	150 lm/W

## MECHANICS

Colour of the housing	light grey
Dimensions LxWxH/DxH	1200 x 87 x 66 mm
Weight (net)	1.7 kg
Cable entry KE X/Y	0 mm / 600 mm
Mounting method	Surface single mounting, Surface light run mounting, Suspended single mounting, Suspended / light run mounting, Wall surface-mounting, Mounting rail mounting

## DEEP-LINK

<https://www.regiolum.de/en/article/50122014100>



Configuration	LED 4100 840
ηLB	100 %
Φ ↓/↑	92 % / 8 %
UGR lat./long.	24.8 / 22.7

