

universal-mounting rail - Universal mounting rail, economical, current taps every 2302.5 mm, for device mount module /2250

Torsion-resistant support rail made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; universal support rail can be used for light runs of all protection types IP20 to IP64; Housing colour traffic white RAL 9016; Heat-resistant, through-wiring with individual conductors installed in the factory. Including 2 current taps for electrical connection of the device mounts, in module 2250. With push connection at the end of the mounting rail for the fast electrical connection of further mounting rails. 2 pre-scored knock-outs at the top allow a direct feed via the mounting rail. Can be optionally equipped with device mounts. Feed adapter and optional mounting rail including outfeed required. Please order assembly accessories as well as rail end pieces and connectors separately.

CHARACTERISTICS

Order number	19284502100
EAN number	4020863423354
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Wiring	7x2.5mm ²
--------	----------------------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	4605mm x 63mm x 46mm
Weight (net)	4.87kg
Type of installation	Mounting rail system installation, Light structure

Dimensions

L	4605 mm	Length
B	63 mm	Width
H	46 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19284502100>

